

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MS 77074A

TABLE I. Dimensional data.

DASH NUMBER	SCREW SIZE	HOLE O A		B	C	D	AWG SIZE
		MAX.	MIN.				
1	4	.127	.115	25/32	5/16	11/64	12
2	6	.153	.141	25/32	5/16	11/64	
3	8	.179	.167	25/32	5/16	11/64	
4	10	.205	.193	51/64	11/32	5/32	TO
5	8	.179	.167	7/8	1/2	11/64	20
6	10	.205	.193	7/8	1/2	11/64	
7	1/4	.285	.258	7/8	1/2	11/64	

(A)

- (A) 1. MATERIAL: Phosphor bronze strip (1.3%tin) alloy C50500, with a minimum temper of H02 in accordance with ASTM B 508. As an alternative material copper, strip alloy C42500, with a minimum temper of H02 may be used.
- (A) 2. FINISH: Electrodeposited tin over entire surface in accordance with MIL-T-10727. Minimum thickness 0.0005. Remove all burrs.
3. DIMENSIONS AND TOLERANCE: Dimensions are in inches. Unless otherwise specified, tolerance is $\pm .015$.
4. The MS part number consists of the MS number plus the Dash number.
5. In the event of a conflict between the text of this Military Specification Sheet and the references cited herein, the text of this Military Specification Sheet shall take precedence.
6. Referenced Government (or non-government) documents of the issue listed in Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this Military Specification Sheet to the extent specified herein.

Custodian:
 Army - AR
 Navy - SH
 Air Force - 85

Preparing Activity:
 Army - AR
 Project Number 5940-1059

Review Activities:
 Army - AV
 Air Force - 11, 99
 DLA - DGSC

User Activities:
 Navy - AS, MC